

LUXMAN

INTEGRATED AMPLIFIER
L-505uX
L-507uX



L-507uX

L-505uX



INTEGRATED AMPLIFIER

L-505uX

L-507uX

L-505uX



LUXMAN have launched the latest generation of transistor integrated amplifier, the 3rd version of the highly rated X series, L-505uX, with a high output power of 100W(8Ω)150W(4Ω). This high performance amplifier introduces Luxman's electronically controlled attenuator LECUA.

Over the last 15 years, since L-505s was first introduced in 1996, it has experienced three times model changes. Now the L-505uX, as the latest full revision model of luxman 506 series, is avidly expected and popularly supported by audiophiles all over the world.

With an illuminated central oriented VU meter on its solid, symmetrical facia, L-505uX introduces a high accuracy electronically controlled attenuator LECUA and Luxman exclusive high sound quality feedback circuit ODNF high S/N version 2.3, while keeping all the other superb features of Luxman products made in Japan.

Specifications

Continuous Outputs:	100W+100W(8Ω), 150W+150W(4Ω)
Input:	line×4, Phono×1(MM/MC), Balance line×1, Recording input/output×1, Separate inputs×1
Loudspeaker Output:	A, B System (A+B output)
Amplifying Circuit Output:	ODNF 2.3
Input Sensitivity/Impedance:	Phono (MM): 2.5mV/47 KΩ, PHONO(MC): 0.3mV/100Ω, LINE: 180mV/47KΩ
Harmonic Distortion:	0.005% or less (1KHz/8Ω), 0.04% or less (20Hz~20KHz/8Ω)
Frequency response:	20Hz~100KHz (+0, -3.0dB)
Signal-to-Noise:	PHONO(MM): >91db, PHONO(MC): >75db, LINE: >105dB
Power Consumption:	270W (rated output), 85W (no signal), 0.4W(idle)
Dimensions (W×H×D):	440×178×454(mm)
Net weight:	22.0kg

※ The right is reserved to alter performance, specification and appearance as required.



L-507uX

Luxman is pleased to announce the L-507uX this merger of transistor amplifier, the 4th version of the highly rated X series, with a high output power of 110W(8 Ω) 220W(4Ω). The L-507uX integrated amplifier introduces Luxman electronically control attenuator LECUA, with an illuminated central oriented VU meter on its solid, symmetrical facia, also includes the Luxman exclusive super sound quality feedback circuit ODNF high S/N version 3.0, while keeping all the superb features of Luxman products made in Japan.

The first L-507-s introduced in 1996, since 16 years, has experienced three times the model after the change, L-507uX as Luxman's new model, with great sales by many users support, belonging to L-500 series full of the latest change model.

Specifications

Continuous Outputs:	110W+110W(8Ω), 220W+220W(4Ω)
Input:	line×4, Phono×1(MM/MC), Balance line×2, Recording input/output×1, Separate inputs×1
Loudspeaker Output:	A, B System (A+B output)
Amplifying Circuit Output:	ODNF 3.0
Input Sensitivity/Impedance:	Phono (MM): 2.5mV/47 KΩ, PHONO(MC): 0.3mV/100Ω, LINE: 180mV/47KΩ, MAIN-IN: 1.05V/47KΩ
Harmonic Distortion:	0.005% or less (1KHz/8Ω), 0.04% or less (20Hz~20KHz/8Ω)
Frequency response:	20Hz~100KHz (+0, -3.0dB)
Signal-to-Noise:	PHONO(MM): >91db, PHONO(MC): >75db, LINE: >105dB
Power Consumption:	300W (rated output), 86W (no signal), 0.4W(idle)
Dimensions (W×H×D):	440×177×454(mm)
Net weight:	23.9kg

※ The right is reserved to alter performance, specification and appearance as required.



LUXMAN

IAG House, Sovereign Court, Ermine Business Park, Huntingdon, Cambs, PE29 6XU, UK
Tel: +44(0)1480 447700 Fax: +44(0)1480 431767 <http://www.luxman.co.jp>

ラックスマン株式会社 〒222-0033 神奈川県横浜市港北区新横浜1-3-1
tel.045-470-6991 fax.045-470-6997 www.luxman.co.jp

IAG reserves the right to alter the design and specifications without notice. All rights reserved © IAG Group Ltd.
Luxman is a member of the International Audio Group. CODE: LN12-LL001

